

Product type designation

TIM 3V-IE

SINAUT ST7, TIM 3V-IE communication module for SIMATIC S7-300 with an RS232 interface for SINAUT communication via a classic WAN and an RJ45 interface for SINAUT communication via an IP-based network (WAN or LAN)



Transmission rate

Transfer rate

- | | |
|---------------------------|--------------------|
| • for Industrial Ethernet | 10 ... 100 Mbit/s |
| • acc. to RS 232 | 50 ... 38400 bit/s |

Interfaces

Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
• for external data transmission / acc. to RS 232	1
• for power supply	1
Type of electrical connection	
• of Industrial Ethernet interface	RJ45 port
• at interface 1 / for external data transmission	9 pin Sub-D-connector (RS232)
• for power supply	2-pole plugable terminal block
design of the removable storage / C-PLUG	No

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	24 V

Supply voltage	20.4 ... 28.8 V
Supply voltage / external / at DC / Rated value	24 V
Supply voltage / external / at DC / rated value	20.4 ... 28.8 V
Relative symmetrical tolerance / at DC	
• at 5 V	5 %
Relative positive tolerance / at DC / at 24 V	5 %
Relative negative tolerance / at DC / at 24 V	5 %
Consumed current	
• from backplane bus / at DC / at 24 V / maximum	0.2 A
• from external supply voltage / at DC / at 24 V / maximum	0.2 A
Power loss [W]	5.8 W
Product extension / optional / Backup battery	No

Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 single width
Width	40 mm
Height	125 mm
Depth	120 mm
Net weight	0.25 kg

Product properties, functions, components / general

Number of units	
• per CPU / maximum	1
• Note	Number of TIM per S7-300
Wire length	
• with RS 232 interface / maximum	6 m

Performance data / S7 communication

Number of possible connections / for S7 communication	
• maximum	8
• with PG connections / maximum	2
• with OP connections / maximum	8
Service	
• SINAUT ST7 via S7 communication	Yes

- PG/OP communication

Yes

Performance data / multi-protocol mode

Number of active connections / with multi-protocol mode

12

Performance data / telecontrol

Suitability for use

- Node station
- substation
- TIM control center
- Note

No
Yes
No
RS232 and Industrial Ethernet can not be operated in parallel

Protocol / is supported

- TCP/IP
- DNP3
- SINAUT ST1 protocol
- SINAUT ST7 protocol

Yes
No
Yes
Yes

Product function / data buffering if connection is aborted

Yes; 16,000 data messages

Storage capacity

- of S7 CPU RAM / for TD7onCPU mode data blocks on CPU / required
- of S7 CPU RAM / for TD7onTIM mode data blocks on TIM / required
- Note

20 Kibyte
0 Kibyte
TD7onCPU: at least 20 KB, actual requirement determined by data volume and functional scope TD7onTIM: 0 bytes in most favorable case

Product feature / Buffered message frame memory

No

Transmission format

- for SINAUT ST1 protocol with polling / 11 bit
- for SINAUT ST1 protocol with spontaneous / 10-bit or 11-bit
- for SINAUT ST7 protocol with multi-master polling / 10-bit
- for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit

Yes
Yes
Yes
Yes

Operating mode for scanning of data transmission

- with dedicated line/radio link / with SINAUT ST1 protocol
- with dedicated line/radio link / with SINAUT ST7 protocol
- with dial-up network / with SINAUT ST1 protocol
- with dial-up network / with SINAUT ST7 protocol

Polling, polling with time slot procedure
Polling, polling with time slot procedure, multi-master polling with time slot procedure
spontaneous
spontaneous

Hamming distance	
<ul style="list-style-type: none"> • for SINAUT ST1 protocol • for SINAUT ST7 protocol 	4 4
Configuration software	
<ul style="list-style-type: none"> • required • for CPU configuring / required / SINAUT TD7 block library for CPU • for PG configuring / required / SINAUT ST7 configuration software for PG 	SINAUT ST7 ES Yes Yes
Storage location / of TIM configuration data	on the TIM

Product functions / Security

Suitability for operation / Virtual Private Network	Yes
Operating mode Virtual Private Network / note	VPN operation as MSC client with MSC protocol and password protection only possible in conjunction with GPRS modem with MSC capability
Type of authentication / with Virtual Private Network / PSK	Yes
Product function	
<ul style="list-style-type: none"> • password protection for VPN • MSC client via GPRS modem with MSC capability 	Yes Yes
Protocol	
<ul style="list-style-type: none"> • is supported / MSC protocol 	No
Key length / for MSC / with Virtual Private Network	128 bit
Number of possible connections	
<ul style="list-style-type: none"> • as MSC client / with VPN connection • as MSC server / with VPN connection 	1 0

Accessories

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

07/10/2018