

SIMATIC S7-300, Digital input SM 321, isolated, 16 DI, 24-48 V AC/DC with single rooting, 1x 40-pole



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	24 V
• permissible range, upper limit (DC)	48 V
Load voltage L1	
• Rated value (AC)	24 V
• permissible range, lower limit (AC)	24 V
• permissible range, upper limit (AC)	48 V
Input current	
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	1.5 W; at 24 V; 2,8 W at 48 V
Digital inputs	
Number of digital inputs	16

Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	16
— up to 60 °C, max.	16
vertical installation	
— up to 40 °C, max.	16
Input voltage	
• Type of input voltage	AC/DC
• Rated value (DC)	24 V; DC 24 or 48 V
• Rated value (AC)	24 V; 24 V AC or 48 V AC (0 ... 63 Hz)
• for signal "0"	-5V AC to +5V AC
• for signal "1"	14V AC to 60V AC
Input current	
• for signal "1", typ.	2.7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	16 ms
— at "0" to "1", max.	16 ms
— at "1" to "0", max.	16 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Diagnostic functions	No
Alarms	
• Diagnostic alarm	No
• Hardware interrupt	No
Diagnostics indication LED	
• Group error SF (red)	No
• Status indicator digital input (green)	Yes

Potential separation

Potential separation digital inputs

- | | |
|--|------------------|
| • between the channels | Yes |
| • between the channels, in groups of | 1 |
| • between the channels and backplane bus | Yes; Optocoupler |

Permissible potential difference

between different circuits	170 V DC/120 V AC
----------------------------	-------------------

Isolation

Isolation tested with	1500 V AC
-----------------------	-----------

Connection method

required front connector	40-pin
--------------------------	--------

Dimensions

Width	40 mm
-------	-------

Height	125 mm
--------	--------

Depth	120 mm
-------	--------

Weights

Weight, approx.	260 g
-----------------	-------

last modified:	07/17/2018
-----------------------	------------